

3395 SERIES NIOSH APPROVED N95 RESPIRATORS

1. **Item No. :** 3395 N95 Particulate Respirator.
3395V N95 Particulate Respirator with Exhalation Valve

2. **Standards :** Federal Register 42 CFR Part 84, as class N95.

3. Applications :

N95 disposable particulate respirators are approved with filtration 95% effective against particulate aerosols free of oils. Conforms to NIOSH 42 CFR Part 84 standard as N95 class.

Recommended applications : textile industry, craft work, iron and steel industry, mining, underground civil engineering and woodworking, hospital, laboratory, and disease control ...etc.

N95 respirators can provide protection against particulate aerosols free of oils containing the following materials such as : china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hard wood, coal, iron ore, aluminum, bacteria and mycobacterium tuberculosis (T.B.).

4. Product Description :

3395 series particulate respirators are NIOSH N95 certified single-use disposable respirators with NIOSH approval according to U.S. Federal Register 42 CFR Part 84.

Manufacturer : San Huei United Co., Ltd. with ISO-9001 and ISO-14001 certification which are both issued by BSI (British Standards Institution).

4.1 3395 N95 Particulate Respirator (NIOSH Approval No. TC-84A-3713)

N95 : filtration 95% effective against particulate aerosols free of oils.

4.2 3395V N95 Particulate Respirator with Exhalation Valve (NIOSH Approval No. TC-84A-3714)

N95 : filtration 95% effective against particulate aerosols free of oils.

Features exhalation valve for extra comfort in hot environment and reduce hot air build up.

5. Material :

- 5.1 Outer Layer : Polypropylene Fabric.
- 5.2 Filter Media : Melt-Blown (Polypropylene).
- 5.3 Inner Layer : Polyester Fabric.
- 5.4 Nose Piece : Aluminium.
- 5.5 Nose Pad : PE Foam.
- 5.6 Headband : Latex-Free Synthetic Rubber.
- 5.9 Exhalation Valve : (for 3395V)
 - Valve Housing : Polypropylene.
 - Valve Membrane : Synthetic Rubber.

6. Dimension :

- 6.1 Respirator : 139 X 127 X 54 mm (LxWxH).
- 6.2 Nose Piece : 90 X 5 X 0.5 mm (LxWxT).
- 6.3 Nose Pad : 100 X 27 X 1.5 mm (WxHxT).
- 6.4 Exhalation Valve : 41 mm (diameter) X 11 mm (H).
- 6.5 Headband :
 - Upper Headband : 300 X 5 X 0.55 mm (LxWxT).
 - Lower Headband : 265 X 5 X 0.55 mm (LxWxT).